


Product Name: AAC block adhesive

Description: Cementous AAC block adhesive

Technical data

Product code: CM2006, CM2007	Item	Feature	Test method	Unit	Standard values	Typical result
	1	Color	visual	*	*	White/Grey
	2	Initial adhesion strength	INSO 12492-1	N/mm ²	≥ 0.5	0.6
	3	Adhesion strength after immersion in water	INSO 12492-1	N/mm ²	≥ 0.5	0.55
	4	Adhesion strength after heat ageing	INSO 12492-1	N/mm ²	≥ 0.5	0.56
	5	Adhesion strength after freeze-thaw cycles	INSO 12492-1	N/mm ²	≥ 0.5	0.51

The given data is stated in standard conditions and can have changes in different workshop conditions and various type of substrate.

Tips, details, and features

- In accordance with the Iran national standard INSO 12942-1 in the C1 class, and compatible with the international standard EN12004.
- A very suitable alternative to traditional mortars.
- Designed for making bond between two AAC blocks.

All information based on technical knowledge and existing standards has been obtained and presented in standard environmental conditions. The policy and organizational strategy of Sepidgach Saveh Company is in line with the research and development and qualitative growth of products, and in this regard, the company reserves the right to change technical data at any time. In case of any changes in the technical specifications, the previously published data will be invalid and the new data will be provided to you through the company's website. Obviously, the commitment of this company is limited to the correct use of the product in suitable environmental conditions in accordance with published standards and guidelines. It should be noted that all the engineering technical knowledge, standards and methods of use are not included in this sheet and the executives are obliged to apply all the executive technical orders separately.