


## Product Name: Tile grout

**Description: Ready to use and premixed tile grout**

### Technical data

Product code: CM2013, CM2014, and CM2015	Item	Feature	Test method	Unit	Standard values	
	1	color	visual	*	Various colors	
	2	fineness	INSO 10760-3, INSO 13007-3	Residue on sieve (max)	0.2 mm	*
					0.1 mm	*
	3	Working time	INSO 10760-3, INSO 13007-3	Minutes	≥ 60	
	4	Bending strength	INSO 10760-3, INSO 13007-3	MPa	≥ 2.5	
	5	Compressive Strength	INSO 10760-3, INSO 13007-3	MPa	≥ 15	
	6	Water absorption after 30 minutes	INSO 10760-3, INSO 13007-3	g	≤ 2	
	7	Water absorption after 30 minutes	INSO 10760-3, INSO 13007-3	g	≤ 5	
8	retraction	INSO 10760-3, INSO 13007-3	mm/m	≤ 3		

The given data is stated in standard conditions and can have changes in different workshop conditions and various type of substrate.

### Tips, details, and features

- In accordance with the Iran national standard INSO 10760-3 and INSO 13007-3.
- Very high adhesion.
- Low water absorption.
- Very high wear resistance.
- In a variety of improved working time, waterproof, and waterproof-antibacterial.
- Very fine.
- Suitable for grouting all kinds of floor and wall tiles in the interior and exterior of the buildings.
- In various color.
- Suitable for the width of the gap between the tiles from 2 to 20 mm.

### Consumption rate

It is determined according to the width and depth of the gaps between the tiles.

All information based on technical knowledge and existing standards has been obtained and presented in standard environmental conditions. The policy and organizational strategy of Sepidgach Saveh Company is in line with the research and development and qualitative growth of products, and in this regard, the company reserves the right to change technical data at any time. In case of any changes in the technical specifications, the previously published data will be invalid and the new data will be provided to you through the company's website. Obviously, the commitment of this company is limited to the correct use of the product in suitable environmental conditions in accordance with published standards and guidelines. It should be noted that all the engineering technical knowledge, standards and methods of use are not included in this sheet and the executives are obliged to apply all the executive technical orders separately.